

S SERIES - S60/S80/S100/S120

S150/S162

SLP SERIES - SLP50/SLP60/SLP80



**Tier 4 Final, 74 hp diesel engine does not require exhaust aftertreatment.
No diesel exhaust fluid and no diesel particulate filter required reducing operating costs.**

- ECOMAX T4 engine
- 4-speed transmission (3-speed in S120) with fully synchronized torque converter.
- Sellick SEE-THRU® sideshifting mast design lifts up to 30 feet.
- Lift capacities of 6,000, 8,000, 10,000, & 12,000 lbs @ 24" load center.

Overall length (without forks)	S60 / S80 149"/150" (3,785 mm/3,810 mm)	S100 / S120 152"/159" (3,861 mm/4,039 mm)
Overall width	89" (2,261 mm)	
Height to top of overhead guard	97" (2,464 mm)	
Turning radius	178" (4,521 mm)	183 " (4,648 mm) (S120 only)
Frame underclearance	15" (381 mm)	

- ECOMAX T4 Engine
- Fully automatic powershift transmission available in 2WD and 4WD.
- 12-bolt pattern rigid drive axle for high-hour, heavy duty applications.
- Lift capacity of 15,000 lbs OR 16,000 @ 24" load center.

Overall length (without forks)	173" (4,395 mm)
Overall width	91" (2,311 mm)
Height to top of overhead guard	101" (2,565 mm)
Turning radius	209" (5,309 mm)
Frame underclearance	18" (457 mm)

- KOHLER KDI 2504 TCR Engine
- Low profile design with narrow width for operation in tight quarters.
- Four-speed transmission with fully synchronized torque converter. 4-speed fully automatic powershift transmission standard on 4WD models.
- Lift capacity of 5,000, 6,000, & 8000 lbs @ 24" load center.

Overall length (without forks)	SLP50 / SLP60 147" (3,734 mm)	SLP80 152" (3,861 mm)
Overall width	78" (1,981 mm)	
Height to top of overhead guard	75" (1,905 mm) 85" (2,195 mm)	
Turning radius	2WD - 178" (4,521 mm) 4WD - 196" (4,978 mm)	
Frame underclearance	11" (279 mm)	

STT80



- ECOMAX T4 final diesel engine, 74 hp - does not require exhaust aftertreatment.
- High torque at low speeds - 295 ft. lbs @ 1,200 RPM
- No diesel exhaust fluid OR particulate filter required reducing operating costs.
- 90° hitch access with excellent visibility, sliding pin hookup & 3" pintle hitch.
- Fully automatic transmission.
- Lift capacity of 13,000 lbs @ 12" load center
- Various hitch & carriage options for any application

Overall length (without forks)	157" (3,988 mm)
Overall width	89" (2,261 mm)
Height to top of overhead guard	97" (2,413 mm)
Turning radius	178" (4,521 mm)
Frame underclearance	15" (381 mm)

OPTIONS & ACCESSORIES

- Sound-suppressed cabs
- Factory-installed air conditioning
- Powershift transmission
- Engine block heater
- Strobe light
- Hydraulic fork positioning carriage
- Rear view mirrors for added safety
- Fork-mounted or carriage-mounted buckets
- Custom paint
- Anti-vandalism package
- AM/FM radio with MP3 player
- Variety of carriage widths and forks for any application

Sold & Serviced By:



800.248.9253 www.bbfyale.com



Sellick Equipment Limited

2131 Roseborough Rd
Harrow, Ontario, Canada N0R 1G0
Telephone: 519-738-2255
Fax: 519-738-3477
Website: www.sellickequipment.com



Because of our constant dedication to product improvement, all specifications are subject to change without notice.

SELICK FORKLIFTS



**RUGGED
POWERFUL
INNOVATIVE**